

GATOR INFLATOR MID DIGITAL

Tire inflator digital

■ Digital & Calibrated

Legally compliant, accurate, and easy to read – a must-have for every workshop.

■ TPMS-Optimized

Precise pressure adjustment to two decimal places – ideal for TPMS service.

■ Built for the workshop

Compatible with all replacement hoses. With drop protection & one-handed operation.

■ ...and all this at an **attractive price.**



Article number	9-149993						
Quality standard	Calibrated, type-approved & workshop-approved based on DIN EN 12645.						
Pressure gauge	Digital pressure gauge with illumination LCD with automatic switchoff function after 90 seconds Ø 80 mm, with rubber protective cap, pressure-resistant up to 15 bar						
Pressure gauge display accuracy	Reading accuracy: 0,01 bar - ideal for TPMS Values according to DIN EN 12645 <table border="0" style="width: 100%;"> <tr> <td style="width: 50%;">pm ≤ 4 bar (58,01 psi):</td> <td style="width: 50%;">±0,08 bar (1,16 psi)</td> </tr> <tr> <td>4 bar (58,01 psi) < pm ≤ 10 bar (145,04 psi):</td> <td>±0,16 bar (2,32 psi)</td> </tr> <tr> <td>pm > 10 bar (145,03 psi):</td> <td>±0,25 bar (3,63 psi)</td> </tr> </table>	pm ≤ 4 bar (58,01 psi):	±0,08 bar (1,16 psi)	4 bar (58,01 psi) < pm ≤ 10 bar (145,04 psi):	±0,16 bar (2,32 psi)	pm > 10 bar (145,03 psi):	±0,25 bar (3,63 psi)
pm ≤ 4 bar (58,01 psi):	±0,08 bar (1,16 psi)						
4 bar (58,01 psi) < pm ≤ 10 bar (145,04 psi):	±0,16 bar (2,32 psi)						
pm > 10 bar (145,03 psi):	±0,25 bar (3,63 psi)						
Pressure gauge measuring range	0 - 12 bar / 0 - 170 psi						
Maximum pressure	12 bar / 170 psi						
Connection	Compressed air supply DN 7.2 Hose connection G1/4						
Filling hose	Rotatable, 1 m (replaceable)						
Connector	Versatile clip-on air chuck						
Battery	2x AAA (replaceable)						
Weight	ca. 800 g (without hose)						
Temperature range	-10°C to +40°C						
Protection class	IP 44						



>> User manual



>> EU Declaration of Conformity

ALLIGATOR is a strong brand of WEGMANN automotive.

Find more info under alligator-valves.com