

TYRE MOUNTING PASTE

Black

High lubricity

Reduced effort and time required due to simple (dis)assembly of the tyres.

Firm tyre fit

Tyre migration is prevented by frictional connection between rim and tyre.

■ The right solution for every need

Available in three viscosities: soft, universal, hard.

| Color | Black | | |
|--------------------------------|--|--|--|
| Content | 5 kg | | |
| Packaging | Bucket | | |
| Lubricity | High | | |
| Drying behavior | Fast drying (ideal for fast processing of a tyre) | | |
| Application temperature | -15 to +50°C | | |
| Environmental compatibility | Biodegradable, vegan & chemically neutral towards rubber, steel & aluminum | | |
| Vehicle type | at a the the test of t | | |



| Viscosity | Soft | Universal | Hard |
|----------------|---|--|--------------------------------------|
| Article number | 3401-0503-101 | 3401-0505-101 | 3401-0507-101 |
| | Time-saving. | | Cost-efficient. |
| Application | Easy brush pick-up. | Moderate brush pick-up. | Economical brush pick-up. |
| | Ideal for large-area, light brush application. | Easy to dose & apply. | Ideal for precise dosing. |
| Yield | Approx. 350 tyres | Approx. 400 tyres | Approx. 450 tyres |
| Note | Ideal for cold ambient temperatures. | Ideal for moderate ambient temperatures. | Ideal for warm ambient temperatures. |