

Safety Data Sheet

According to Regulation (EC) No. 1272/2008 (CLP), as amended by Commission Regulation (EU) 2019/521 and Commission Delegated Regulation (EU) 2020/217, and (EC) No. 1907/2006 (REACH)

Initial preparation date: 06.04.2021

Page 1 of 22

Maxibond Blue Cement

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product Name: Maxibond Blue Cement (235ml & 945ml)

Product code: H-658F/8oz / H-658F/QT

Additional information: Version 1

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: Rubber Cement

Uses advised against: Not determined or not applicable.

Reasons why uses advised against: Not determined or not applicable.

1.3 Details of the manufacturer/supplier of the safety data sheet

Manufacturer:

North America

Tech International
200 East Coshocton Street
Johnstown, OH 43031
1-740-967-9015
www.tech-international.com

Supplier:

European Union

WEGMANN automotive GmbH
Rudolf-Diesel-Strasse 6
DE- 97209 Veitshoechheim - Germany

1.4 Emergency telephone number:

European Union

+49(0)931-321-04-0

SECTION 2: Hazard(s) identification

2.1 Classification of the substance or mixture:

Classification according to Regulation (EC) No. 1272/2008 (CLP):

Flammable liquids, category 2

Skin irritation, category 2

Specific target organ toxicity - single exposure, category 3, central nervous system

Chronic aquatic hazard, category 2

Hazard-determining components of labeling:

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

Heptane

2.2 Label elements

Hazard pictograms:



Signal word: Danger

Hazard statements:

H225 Highly flammable liquid and vapor.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Safety Data Sheet

According to Regulation (EC) No. 1272/2008 (CLP), as amended by Commission Regulation (EU) 2019/521 and Commission Delegated Regulation (EU) 2020/217, and (EC) No. 1907/2006 (REACH)

Initial preparation date: 06.04.2021

Page 2 of 22

Maxibond Blue Cement

Precautionary statements:

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P233 Keep container tightly closed.
- P240 Ground and bond container and receiving equipment.
- P241 Use explosion-proof [electrical/ventilating/lighting] equipment.
- P242 Use non-sparking tools.
- P243 Take action to prevent static discharges.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P264 Wash skin thoroughly after handling.
- P261 Avoid breathing dust/fume/gas/mist/vapors/spray.
- P271 Use only outdoors or in a well-ventilated area.
- P273 Avoid release to the environment.
- P302+P352 IF ON SKIN: Wash with plenty of water/soap.
- P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
- P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P332+P313 If skin irritation occurs: Get medical advice/attention
- P312 Call a POISON CENTER/doctor/physician if you feel unwell.
- P321 Specific treatment (see supplemental first aid instructions on this label).
- P362+P364 Take off contaminated clothing and wash it before reuse.
- P370+P378 In case of fire: Use agents recommended in Section 5 to extinguish.
- P391 Collect spillage
- P403+P235 Store in a well ventilated place. Keep cool.
- P405 Store locked up.
- P403+P233 Store in a well ventilated place. Keep container tightly closed.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3 Other hazards: None known

SECTION 3: Composition/information on ingredients

3.1 Substance: Not applicable.

3.2 Mixture:

Identification	Name	Classification according to Regulation (EC) No. 1272/2008 (CLP)	Weight %
CAS number: 64742-49-0 EC number: 265-151-9 REACH number: 01-2119475515-33-0015	Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	Stot SE 3; H336 Asp. Tox. 1; H304 Aquatic Chronic 2; H411 Skin Irrit. 2 ; H315 Flam. Liq. 2; H225	60-90
CAS number: 142-82-5 EC number: 205-563-8	Heptane	Asp. Tox. 1; H304 Skin Irrit. 2 ; H315 Stot SE 3; H336 Flam. Liq. 2; H225 Aquatic Acute 1; H400 Aquatic Chronic 1; H410	<10
CAS number: 35884-05-0 EC number: 252-774-6	Zinc Dibutyldithiocarbamate/B utylamine Complex	Not classified	<10

Safety Data Sheet

According to Regulation (EC) No. 1272/2008 (CLP), as amended by Commission Regulation (EU) 2019/521 and Commission Delegated Regulation (EU) 2020/217, and (EC) No. 1907/2006 (REACH)

Initial preparation date: 06.04.2021

Page 3 of 22

Maxibond Blue Cement

CAS number: 8042-47-5 EC number: 232-455-8	White Mineral Oil	Not classified	<10
CAS number: 1332-58-7 EC number: 310-194-1	Clay	Not classified	<5
CAS number: 1314-13-2 EC number: 215-222-5 REACH number: 01-2119463881-32-0039	Zinc oxide	Aquatic Acute 1; H400 Aquatic Chronic 1; H410	<5
CAS number: 65997-13-9 EC number: 266-042-9	Glycerol Ester of Partially Hydrogenated Wood Rosin	Not classified	<5
CAS number: 57-11-4 EC number: 200-313-4	Stearic acid	Not classified	<5
CAS number: 13463-67-7 EC number: 236-675-5	Titanium Dioxide	Not classified	<1
CAS number: 14808-60-7 EC number: 238-878-4	Crystalline Silica	Stot RE 1; H372 Carc. 1A; H350	<0.1

Additional information:

Independent testing of Tech International products containing zinc oxide demonstrate that zinc is not appreciably leachable, and therefore does not contribute to an aquatic hazard in the finished form, or levels present in this product.

Full Text of H and EUH statements: See section 16

SECTION 4: First aid measures

4.1 Description of first aid measures

General notes:

Not determined or not available.

Following inhalation:

If inhaled, remove person to fresh air and place in a position comfortable for breathing. Keep person at rest. If breathing is difficult, administer oxygen. If breathing has stopped, provide artificial respiration. If experiencing respiratory symptoms, seek medical advice/attention

Following skin contact:

Remove contaminated clothing and shoes. Rinse skin with copious amounts of water [shower] for several minutes. Launder contaminated clothing before reuse. If symptoms develop or persist, seek medical advice/attention

Following eye contact:

Rinse eyes with plenty of water for several minutes. Remove contact lenses if present and easy to do so. Protect unexposed eye. If symptoms develop or persist, seek medical advice/attention

Following ingestion:

If swallowed, DO NOT induce vomiting unless told to do so by a physician or poison control center. Rinse mouth with water. Never give anything by mouth to an unconscious person. If spontaneous vomiting occurs, place on the left side with head down to prevent aspiration of liquid into the lungs. If symptoms develop or persist, seek medical advice/attention

Safety Data Sheet

According to Regulation (EC) No. 1272/2008 (CLP), as amended by Commission Regulation (EU) 2019/521 and Commission Delegated Regulation (EU) 2020/217, and (EC) No. 1907/2006 (REACH)

Initial preparation date: 06.04.2021

Page 4 of 22

Maxibond Blue Cement

4.2 Most important symptoms and effects, both acute and delayed

Acute symptoms and effects:

Product is highly flammable. Exposure to sources of ignition may cause physical injury

Skin contact may result in redness, pain, burning and inflammation

Inhalation may have adverse effects on the central nervous system. Symptoms may include drowsiness, dizziness, headache, nausea and lowering of consciousness. Acute overexposure via inhalation may result in respiratory distress, confusion and unconsciousness

Delayed symptoms and effects:

Effects are dependent on exposure (dose, concentration, contact time).

4.3 Indication of any immediate medical attention and special treatment needed

Specific treatment:

Skin/eye burns require immediate treatment.

Overexposure via inhalation requires urgent medical treatment.

Notes for the doctor:

Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media:

Use Water (fog only), dry chemical, chemical foam, carbon dioxide, or alcohol-resistant foam.

Unsuitable extinguishing media:

Do not use a water stream as an extinguisher.

5.2 Special hazards arising from the substance or mixture:

Highly flammable liquid. Will be easily ignitable by heat, sparks or flames. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks). Vapor explosion hazard indoors, outdoors or in sewers. Runoff to sewer may create fire or explosion hazard. Containers may explode when heated. Inhalation or contact with material may irritate or burn skin and eyes. Fire may produce irritating, corrosive and/or toxic gases. Vapors may cause dizziness or suffocation.

5.3 Advice for firefighters

Personal protection equipment:

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full-face piece operated in positive pressure mode.

Special precautions:

Evacuate non-essential personnel. Ventilate closed spaces before entering. Consider initial evacuation for 300 meters in all directions. If tank/rail car is involved in the fire, ISOLATE for 800 meters in all directions. Fight fire from a maximum distance. Move containers from fire area if you can do it without risk. Use water spray/fog for cooling fire exposed containers. Withdraw immediately in case of rising sound from venting safety devices or discoloration of tank. Always stay away from tanks engulfed in fire. For massive fire, use unmanned hose holders or monitor nozzles. If this is impossible, withdraw from area and let fire burn. Stand by, at a safe distance, with extinguisher ready for possible re-ignition. A vapor-suppressing foam may be used to reduce vapors. Avoid unnecessary run-off of extinguishing media which may cause pollution. Do not handle damaged containers unless specialized to do so.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures:

Evacuate unnecessary personnel. Ventilate area. Extinguish any sources of ignition. All equipment used when handling the product must be grounded. Wear recommended personal protective equipment (see Section 8). Avoid contact with skin, eyes and clothing. Avoid breathing mist, vapor, dust, fume and spray. Do not walk through spilled material. Wash thoroughly after handling.

Safety Data Sheet

According to Regulation (EC) No. 1272/2008 (CLP), as amended by Commission Regulation (EU) 2019/521 and Commission Delegated Regulation (EU) 2020/217, and (EC) No. 1907/2006 (REACH)

Initial preparation date: 06.04.2021

Page 5 of 22

Maxibond Blue Cement

6.2 Environmental precautions:

Prevent further leakage or spillage if safe to do so. Prevent from reaching drains, sewers and waterways. Discharge into the environment must be avoided.

6.3 Methods and material for containment and cleaning up:

Do not touch damaged containers or spilled material unless wearing appropriate personal protective clothing. Stop leak if you can do it without risk. A vapor-suppressing foam may be used to reduce vapors. Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers for future disposal. Dispose of in accordance with all applicable regulations (see Section 13).

6.4 Reference to other sections:

For personal protective equipment see Section 8. For disposal see Section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling:

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof electrical, ventilating and lighting equipment. Take action to prevent static discharges. Handle containers with caution. Use appropriate personal protective equipment (see Section 8). Use only with adequate ventilation. Avoid breathing mist/vapor/spray/dust. Do not eat, drink, smoke, or use personal products when handling chemical substances. Avoid contact with skin, eyes and clothing. Wash affected areas thoroughly after handling. Keep away from incompatible materials (See Section 10). Keep containers tightly closed when not in use.

7.2 Conditions for safe storage, including any incompatibilities:

Store in cool, dry, well-ventilated location out of direct sunlight. Keep away from food and beverages. Protect from freezing and physical damage. Store away from heat, open flames and other sources of ignition. Keep container tightly sealed. Store away from incompatible materials (See Section 10).

7.3 Specific end use(s):

Refer to Section 1 (Recommended Use)

SECTION 8: Exposure controls/personal protection



8.1 Control parameters

Only those substances with limit values have been included below.

Occupational Exposure limit values:

Country (Legal Basis)	Substance	Identifier	Permissible concentration
Poland	Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	64742-49-0	STEL: 1500 mg/m ³
	Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	64742-49-0	TWA: 500 mg/m ³
	Heptane	142-82-5	8-hour TWA (NDS): 1200 mg/m ³
	Heptane	142-82-5	15-minute STEL (NDSCh): 2000 mg/m ³
	Zinc oxide	1314-13-2	8-hour TWA (NDS): 5 mg/m ³ (Inhalable fraction, as Zn)
	Zinc oxide	1314-13-2	15-minute STEL (NDSCh): 10 mg/m ³ (Inhalable fraction, as Zn)
	Titanium Dioxide	13463-67-7	OEL: TWA (NDS) 10.0 mg/m ³ 8-hr

Safety Data Sheet

According to Regulation (EC) No. 1272/2008 (CLP), as amended by Commission Regulation (EU) 2019/521 and Commission Delegated Regulation (EU) 2020/217, and (EC) No. 1907/2006 (REACH)

Initial preparation date: 06.04.2021

Page 6 of 22

Maxibond Blue Cement

Country (Legal Basis)	Substance	Identifier	Permissible concentration
	Clay	1332-58-7	8-hour TWA: 6 mg/m ³
	White Mineral Oil	8042-47-5	8-hour TWA (NDS): 5 mg/m ³ (Highly refined mineral oils with the exception of cutting fluids, Inhalable fraction)
	Crystalline Silica	14808-60-7	8-hour TWA (NDS): 2 mg/m ³ (dusts containing more than 50% free crystalline silica, inhalable fraction)
	Crystalline Silica	14808-60-7	8-hour TWA (NDS): 0.3 mg/m ³ (dusts containing more than 50% free crystalline silica, respirable fraction)
	Crystalline Silica	14808-60-7	8-hour TWA (NDS): 4 mg/m ³ (dusts containing from 2% to 50% free crystalline silica, inhalable fraction)
	Crystalline Silica	14808-60-7	8-hour TWA (NDS): 1 mg/m ³ (dusts containing from 2% to 50% free crystalline silica, respirable fraction)
Bulgaria	Heptane	142-82-5	TWA: 1600 mg/m ³
	Zinc oxide	1314-13-2	TWA: 5.0 mg/m ³
	Zinc oxide	1314-13-2	15-minute STEL: 10.0 mg/m ³
	Titanium Dioxide	13463-67-7	OEL: TWA 10.0 mg/m ³ (Respirable dust)
	Clay	1332-58-7	TWA: 6.0 mg/m ³ (inhalable fraction)
	Clay	1332-58-7	TWA: 3.0 mg/m ³ (respirable fraction)
	White Mineral Oil	8042-47-5	TWA: 5.0 mg/m ³ (petroleum)
	Crystalline Silica	14808-60-7	TWA: 0.07 mg/m ³ (free silicon dioxide, crystalline and quartz glass, respirable fraction)
Croatia	Heptane	142-82-5	Maximum (8 hr) allowable concentration: 500 ppm (2085 mg/m ³)
	Glycerol Ester of Partially Hydrogenated Wood Rosin	65997-13-9	Maximum (8 hr) allowable concentration: 0.05 mg/m ³
	Glycerol Ester of Partially Hydrogenated Wood Rosin	65997-13-9	Short-term (15 min) allowable concentration: 0.15 mg/m ³
	Zinc oxide	1314-13-2	Maximum (8 hr) allowable concentration: 5 mg/m ³
	Zinc oxide	1314-13-2	Short-term (15 min) allowable concentration: 10 mg/m ³
	Titanium Dioxide	13463-67-7	OEL: TWA 10.0 mg/m ³ (Total dust) 15-min
	Titanium Dioxide	13463-67-7	OEL: TWA 4.0 mg/m ³ (Respirable dust) 15-min
	Clay	1332-58-7	Maximum (8 hr) allowable concentration: 2 mg/m ³ (respirable dust)

Safety Data Sheet

According to Regulation (EC) No. 1272/2008 (CLP), as amended by Commission Regulation (EU) 2019/521 and Commission Delegated Regulation (EU) 2020/217, and (EC) No. 1907/2006 (REACH)

Initial preparation date: 06.04.2021

Page 7 of 22

Maxibond Blue Cement

Country (Legal Basis)	Substance	Identifier	Permissible concentration
	Crystalline Silica	14808-60-7	Maximum (8 hr) allowable concentration: 0.1 mg/m ³ (crystalline SiO ₂ [quartz])
Czech Republic	Heptane	142-82-5	8-hour TWA: 1000 mg/m ³
	Heptane	142-82-5	Ceiling limit (NPK-P): 2000 mg/m ³
	Glycerol Ester of Partially Hydrogenated Wood Rosin	65997-13-9	8-hour TWA: 4 mg/m ³
	Zinc oxide	1314-13-2	8-hour TWA: 2 mg/m ³ (as Zn)
	Zinc oxide	1314-13-2	Ceiling limit (NPK-P): 5 mg/m ³ (Fumes)
	Clay	1332-58-7	8-hour TWA: 5.0 mg/m ³
	White Mineral Oil	8042-47-5	8-hour TWA: 5 mg/m ³ (aerosol)
	White Mineral Oil	8042-47-5	Ceiling limit (NPK-P): 10 mg/m ³ (aerosol)
	Crystalline Silica	14808-60-7	8-hour TWA: 0.1 mg/m ³ (quartz, dust, respirable fraction)
Estonia	Heptane	142-82-5	8-hour TWA: 500 ppm (2085 mg/m ³)
	Zinc oxide	1314-13-2	8-hour TWA: 5 mg/m ³
	Titanium Dioxide	13463-67-7	OEL: TWA 5 mg/m ³ 8-hr
	Clay	1332-58-7	8-hour TWA: 10 mg/m ³ (total dust)
	Clay	1332-58-7	8-hour TWA: 5 mg/m ³ (fine dust)
	Crystalline Silica	14808-60-7	8-hour TWA: 0.1 mg/m ³ (quartz, fine dust)
Hungary	Heptane	142-82-5	8-hour TWA (ÁK Value): 2000 mg/m ³
	Heptane	142-82-5	60-minute STEL (CK value): 8000 mg/m ³
	Zinc oxide	1314-13-2	8-hour TWA (ÁK Value): 5 mg/m ³ (Respirable)
	Zinc oxide	1314-13-2	60-minute STEL (CK Value): 20 mg/m ³ (Respirable)
	Clay	1332-58-7	8-hour TWA (ÁK Value): 10 mg/m ³ (total, inhalable)
	Clay	1332-58-7	8-hour TWA (ÁK Value): 5 mg/m ³ (Respirable)
	White Mineral Oil	8042-47-5	Ceiling Limit (MK Value): 5 mg/m ³ [Oil smog (mineral oil)]
	Crystalline Silica	14808-60-7	8-hour TWA (ÁK Value): 0.15 mg/m ³ (quartz, respirable)
Latvia	Heptane	142-82-5	8-hour TWA: 350 mg/m ³ (85 ppm)
	Heptane	142-82-5	15-minute STEL: 2085 mg/m ³ (500 ppm)
	Zinc oxide	1314-13-2	8-hour TWA: 0.5 mg/m ³
	Titanium Dioxide	13463-67-7	OEL: TWA 10.0 mg/m ³ 8-hr
	Clay	1332-58-7	8-hour TWA: 2 mg/m ³

Safety Data Sheet

According to Regulation (EC) No. 1272/2008 (CLP), as amended by Commission Regulation (EU) 2019/521 and Commission Delegated Regulation (EU) 2020/217, and (EC) No. 1907/2006 (REACH)

Initial preparation date: 06.04.2021

Page 8 of 22

Maxibond Blue Cement

Country (Legal Basis)	Substance	Identifier	Permissible concentration
Lithuania	Heptane	142-82-5	8-hour TWA: 2085 mg/m ³ (500 ppm)
	Heptane	142-82-5	15-minute STEL: 3128 mg/m ³ (750 ppm)
	Zinc oxide	1314-13-2	8-hour TWA: 5 mg/m ³
	Stearic acid	57-11-4	8-hour TWA: 5 mg/m ³
	Titanium Dioxide	13463-67-7	OEL: TWA 5 mg/m ³ 8-hr
	Clay	1332-58-7	8-hour TWA: 10 mg/m ³ (inhalable fraction)
	Clay	1332-58-7	8-hour TWA: 5 mg/m ³ (respirable fraction)
	White Mineral Oil	8042-47-5	8-hour TWA: 1 mg/m ³ (Oil mist, including smoke)
	White Mineral Oil	8042-47-5	15-minute STEL: 3 mg/m ³ (Oil mist, including smoke)
	Crystalline Silica	14808-60-7	8-hour TWA: 0.1 mg/m ³ [quartz (silicon dioxide form), respirable fraction]
Slovakia	Zinc Dibutyldithiocarbamate/Butylamine Complex	35884-05-0	8-hour TWA (NPEL): 0.1 mg/m ³ (respirable fraction)
	Zinc Dibutyldithiocarbamate/Butylamine Complex	35884-05-0	8-hour TWA (NPEL): 2 mg/m ³ (inhalable fraction)
	Heptane	142-82-5	8-hour TWA (NPEL): 500 ppm (2085 mg/m ³)
	Zinc oxide	1314-13-2	8-hour TWA (NPEL): 1 mg/m ³ [Fumes (Respirable fraction)]
	Zinc oxide	1314-13-2	15-minute STEL (NPEL): 1 mg/m ³ [Fumes (Respirable fraction)]
	Zinc oxide	1314-13-2	8-hour TWA (NPEL): 0.1 mg/m ³ [Zinc and its inorganic compounds (Respirable fraction)]
	Zinc oxide	1314-13-2	8-hour TWA (NPEL): 2 mg/m ³ [Zinc and its inorganic compounds (Inhalable fraction)]
	Titanium Dioxide	13463-67-7	OEL: TWA (NPEL) 5 mg/m ³ 8-hr
	Clay	1332-58-7	8-hour TWA (NPEL): 2 mg/m ³
	White Mineral Oil	8042-47-5	8-hour TWA (NPEL): 5 ppm (1 mg/m ³) [Liquid mineral oil mist, fumes]
	White Mineral Oil	8042-47-5	15-minute STEL (NPEL): 15 ppm (3 mg/m ³) [Liquid mineral oil mist, fumes]
	Crystalline Silica	14808-60-7	8-hour TWA (NPEL): 0.1 mg/m ³ (silica)
	Crystalline Silica	14808-60-7	8-hour TWA: 0.1 mg/m ³ (silicon dioxide, crystalline, respirable fraction)
Malta	Heptane	142-82-5	TWA: 500 ppm (2085 mg/m ³)
Romania	Heptane	142-82-5	8-hour TWA: 2085 mg/m ³ (500 ppm)

Safety Data Sheet

According to Regulation (EC) No. 1272/2008 (CLP), as amended by Commission Regulation (EU) 2019/521 and Commission Delegated Regulation (EU) 2020/217, and (EC) No. 1907/2006 (REACH)

Initial preparation date: 06.04.2021

Page 9 of 22

Maxibond Blue Cement

Country (Legal Basis)	Substance	Identifier	Permissible concentration
	Glycerol Ester of Partially Hydrogenated Wood Rosin	65997-13-9	8-hour TWA: 0.10 mg/m ³
	Zinc oxide	1314-13-2	8-hour TWA: 5 mg/m ³ (Fumes)
	Zinc oxide	1314-13-2	15-minute STEL: 10 mg/m ³ (Fumes)
	Titanium Dioxide	13463-67-7	OEL: TWA 10.0 mg/m ³ 8-hr
	Titanium Dioxide	13463-67-7	OEL: STEL 15 mg/m ³ 15-min
	Clay	1332-58-7	8-hour TWA: 2 mg/m ³ (inhalable fraction)
	White Mineral Oil	8042-47-5	8-hour TWA: 5 mg/m ³ (Mineral oils)
	White Mineral Oil	8042-47-5	15-minute STEL: 10 mg/m ³ (Mineral oils)
	Crystalline Silica	14808-60-7	8-hour TWA: 0.1 mg/m ³ (quartz, respirable fraction)
	Crystalline Silica	14808-60-7	8-hour TWA: 0.1 mg/m ³ (quartz, dust, respirable fraction)
Slovenia	Heptane	142-82-5	8-hour TWA: 2085 mg/m ³ (500 ppm)
	Zinc oxide	1314-13-2	8-hour TWA: 5 mg/m ³ [Fumes (Respirable fraction)]
	Zinc oxide	1314-13-2	STEL: 20 mg/m ³ [Fumes (Respirable fraction)]
	Crystalline Silica	14808-60-7	8-hour TWA: 0.15 mg/m ³ (quartz, respirable fraction)
European Union	Heptane	142-82-5	IOEL threshold limit: 2085 mg/m ³ (500 ppm)
	Heptane	142-82-5	SCOEL 8-hour TWA: 500 ppm (2085 mg/m ³)
	White Mineral Oil	8042-47-5	SCOEL 8-hour TWA: 5 mg/m ³ (severely refined mineral oils, inhalable)
United Kingdom	Glycerol Ester of Partially Hydrogenated Wood Rosin	65997-13-9	TWA: 0.05 mg/m ³
	Glycerol Ester of Partially Hydrogenated Wood Rosin	65997-13-9	STEL: 0.15 mg/m ³
	Heptane	142-82-5	TWA: 500 ppm (2085 mg/m ³)
	Titanium Dioxide	13463-67-7	OEL: TWA 10.0 mg/m ³ (Total dust)
	Titanium Dioxide	13463-67-7	OEL: TWA 4.0 mg/m ³ (Respirable dust)
	Clay	1332-58-7	TWA: 2 mg/m ³ (respirable dust)
	Crystalline Silica	14808-60-7	TWA: 0.1 mg/m ³ (silica, respirable crystalline)
Belgium	Heptane	142-82-5	8-hour TWA: 400 ppm (1664 mg/m ³)
	Heptane	142-82-5	15-minute STEL: 500 ppm (2085 mg/m ³)
	Zinc oxide	1314-13-2	8-hour TWA: 5 mg/m ³ (Fumes)

Safety Data Sheet

According to Regulation (EC) No. 1272/2008 (CLP), as amended by Commission Regulation (EU) 2019/521 and Commission Delegated Regulation (EU) 2020/217, and (EC) No. 1907/2006 (REACH)

Initial preparation date: 06.04.2021

Page 10 of 22

Maxibond Blue Cement

Country (Legal Basis)	Substance	Identifier	Permissible concentration
	Zinc oxide	1314-13-2	15-minute STEL: 10 mg/m ³ (Fumes)
	Zinc oxide	1314-13-2	8-hour TWA: 10 mg/m ³ (Dusts)
	Stearic acid	57-11-4	8-hour TWA: 10 mg/m ³ (as stearates)
	Titanium Dioxide	13463-67-7	OEL: TWA 10.0 mg/m ³ 8-hr
	Clay	1332-58-7	8-hour TWA: 2 mg/m ³ (respirable fraction)
	Clay	1332-58-7	8-hour TWA: 10 mg/m ³ (inhalable fraction)
	White Mineral Oil	8042-47-5	8-hour TWA: 5 mg/m ³ [Mineral oils (mist)]
	White Mineral Oil	8042-47-5	15-minute STEL: 10 mg/m ³ [Mineral oils (mist)]
	Crystalline Silica	14808-60-7	8-hour TWA: 0.1 mg/m ³ [crystalline silica: quartz (respirable dust)]
Denmark	Heptane	142-82-5	TWA: 200 ppm (820 mg/m ³)
	Zinc oxide	1314-13-2	TWA: 4 mg/m ³
	Titanium Dioxide	13463-67-7	OEL: TWA 6.0 mg/m ³
	Clay	1332-58-7	TWA: 2 mg/m ³
	White Mineral Oil	8042-47-5	TWA: 1 mg/m ³
	Crystalline Silica	14808-60-7	TWA: 0.3 mg/m ³ (total)
	Crystalline Silica	14808-60-7	TWA: 0.1 mg/m ³ (respirable)
Finland	Heptane	142-82-5	8-hour limit: 300 ppm (1200 mg/m ³)
	Heptane	142-82-5	15-minute limit: 500 ppm (2100 mg/m ³)
	Zinc oxide	1314-13-2	8-hour limit: 2 mg/m ³
	Zinc oxide	1314-13-2	15-minute limit: 10 mg/m ³
	Titanium Dioxide	13463-67-7	OEL: TWA 10.0 mg/m ³ 8-hr
	Clay	1332-58-7	8-hour limit: 2 mg/m ³
	White Mineral Oil	8042-47-5	8-hour limit: 5 mg/m ³
	Crystalline Silica	14808-60-7	8-hour limit: 0.05 mg/m ³
France	Heptane	142-82-5	Time weighted average (VME): 400 ppm (1668 mg/m ³)
	Heptane	142-82-5	Short term exposure limit: 500 ppm (2085 mg/m ³)
	Zinc oxide	1314-13-2	Time weighted average (VME): 5 mg/m ³ (Fumes)
	Zinc oxide	1314-13-2	Time weighted average (VME): 10 mg/m ³ (Dusts)
	Titanium Dioxide	13463-67-7	OEL: (VME) 10 mg/m ³
	Clay	1332-58-7	Time weighted average (VME): 10 mg/m ³
	Crystalline Silica	14808-60-7	Time weighted average (VME) 0.1 mg/m

Safety Data Sheet

According to Regulation (EC) No. 1272/2008 (CLP), as amended by Commission Regulation (EU) 2019/521 and Commission Delegated Regulation (EU) 2020/217, and (EC) No. 1907/2006 (REACH)

Initial preparation date: 06.04.2021

Page 11 of 22

Maxibond Blue Cement

Country (Legal Basis)	Substance	Identifier	Permissible concentration
Germany	Heptane	142-82-5	AGW limit value: 500 ppm (2100 mg/m ³)
	Heptane	142-82-5	AGW Short term (15 min) exposure limit: 500 ppm (2100 mg/m ³)
	Clay	1332-58-7	AGW Limit value: 1.25 mg/m ³ (respirable fraction)
	Clay	1332-58-7	AGW limit value: 10 mg/m ³ (inhalable fraction)
	White Mineral Oil	8042-47-5	AGW limit value: 5 mg/m ³
	White Mineral Oil	8042-47-5	AGW Short term (15 min) exposure limit: 20 mg/m ³
Greece	Heptane	142-82-5	8-hour TWA: 500 ppm (2000 mg/m ³)
	Heptane	142-82-5	15-minute STEL: 500 ppm (2000 mg/m ³)
	Zinc oxide	1314-13-2	8-hour TWA: 5 mg/m ³ (Fumes)
	Zinc oxide	1314-13-2	15-minute STEL: 10 mg/m ³ (Fumes)
	Titanium Dioxide	13463-67-7	OEL: TWA 10.0 mg/m ³ (Inhalable) 8-hr
	Titanium Dioxide	13463-67-7	OEL: TWA 5.0 mg/m ³ (Respirable dust) 8-hr
	White Mineral Oil	8042-47-5	8-hour TWA: 5 mg/m ³ [Paraffin oil (Mist)]
Ireland	Heptane	142-82-5	8-hour OEL (TWA): 500 ppm (2085 mg/m ³)
	Stearic acid	57-11-4	8-hour TWA: 10 mg/m ³ (as stearates, except lead stearate)
	Titanium Dioxide	13463-67-7	OEL: TWA 10.0 mg/m ³ (Inhalable dust) 8-hr
	Titanium Dioxide	13463-67-7	OEL: TWA 4.0 mg/m ³ (Respirable dust) 8-hr
	Clay	1332-58-7	8-hour OEL (TWA): 2.0 mg/m ³ (respirable dust)
	White Mineral Oil	8042-47-5	8-hour OEL (TWA): 5 mg/m ³ (Mineral oil, pure, highly and severely refined; Inhalable fraction)
Italy	Heptane	142-82-5	8-hour TWA: 500 ppm (2085 mg/m ³)
	Zinc oxide	1314-13-2	8-hour TWA: 2 mg/m ³ (Respirable fraction)
	Zinc oxide	1314-13-2	15-minute STEL: 10 mg/m ³ (Respirable fraction)
	Stearic acid	57-11-4	8-hour TWA: 3 mg/m ³ [Stearates (except stearates of toxic metals), Respirable fraction]
	Stearic acid	57-11-4	8-hour TWA: 10 mg/m ³ [Stearates (except stearates of toxic metals), Inhalable fraction]

Safety Data Sheet

According to Regulation (EC) No. 1272/2008 (CLP), as amended by Commission Regulation (EU) 2019/521 and Commission Delegated Regulation (EU) 2020/217, and (EC) No. 1907/2006 (REACH)

Initial preparation date: 06.04.2021

Page 12 of 22

Maxibond Blue Cement

Country (Legal Basis)	Substance	Identifier	Permissible concentration
	Titanium Dioxide	13463-67-7	OEL: TWA 10.0 mg/m ³ 8-hr
	Clay	1332-58-7	8-hour TWA: 2 mg/m ³ (Respirable fraction)
	White Mineral Oil	8042-47-5	8-hour TWA: 5 mg/m ³ (Mineral oil, excluding metal working fluids, pure, highly and severely refined; Inhalable fraction)
	Crystalline Silica	14808-60-7	8-hour TWA: 0.025 mg/m ³ (respirable fraction)
Netherlands	Heptane	142-82-5	Binding 8-hour TWA: 1200 mg/m ³
	Heptane	142-82-5	Binding STEL (15 min): 1600 mg/m ³
	White Mineral Oil	8042-47-5	Binding 8-hour TWA: 5 mg/m ³ [Oil mist (Mineral oil)]
	Crystalline Silica	14808-60-7	Binding 8-hour TWA: 0.075 mg/m ³ (respirable dust)
Portugal	Heptane	142-82-5	Decree-Law No. 24/2012 8-hour TWA: 500 ppm (2085 mg/m ³)
	Heptane	142-82-5	NP 1796-2007 8-hour exposure limit: 400 ppm
	Heptane	142-82-5	NP 1796-2007 Short-term exposure limit: 500 ppm
	Zinc oxide	1314-13-2	8-hour exposure limit: 2 mg/m ³
	Zinc oxide	1314-13-2	Short-term exposure limit: 10 mg/m ³
	Stearic acid	57-11-4	8-hour Exposure Limit: 10 mg/m ³ (as stearates)
	Titanium Dioxide	13463-67-7	OEL: TWA 10.0 mg/m ³ 8-hr
	Clay	1332-58-7	8-hour exposure limit: 2 mg/m ³
	White Mineral Oil	8042-47-5	NP 1796-2007 8-hour exposure limit: 5 mg/m ³
	White Mineral Oil	8042-47-5	NP 1796-2007 Short-term exposure limit: 10 mg/m ³
	Crystalline Silica	14808-60-7	8-hour exposure limit: 0.025 mg/m ³
Spain	Heptane	142-82-5	8-hour daily exposure limit (VLA-ED): 500 ppm (2085 mg/m ³)
	Zinc oxide	1314-13-2	8-hour daily exposure limit (VLA_ED): 2 mg/m ³
	Zinc oxide	1314-13-2	15-minute STEL (VLA-EC): 10 mg/m ³
	Stearic acid	57-11-4	8-hour daily exposure limit (VLA_ED): 10 mg/m ³ [Stearates (except stearates of toxic metals)]
	Titanium Dioxide	13463-67-7	OEL: (VLA_ED) 10.0 mg/m ³ 8-hr
	Clay	1332-58-7	8-hour daily exposure limit (VLA_ED): 2 mg/m ³
	White Mineral Oil	8042-47-5	8-hour daily exposure limit (VLA_ED): 5 mg/m ³

Safety Data Sheet

According to Regulation (EC) No. 1272/2008 (CLP), as amended by Commission Regulation (EU) 2019/521 and Commission Delegated Regulation (EU) 2020/217, and (EC) No. 1907/2006 (REACH)

Initial preparation date: 06.04.2021

Page 13 of 22

Maxibond Blue Cement

Country (Legal Basis)	Substance	Identifier	Permissible concentration
	White Mineral Oil	8042-47-5	15-minute STEL (VLA-EC): 10 mg/m ³
	Crystalline Silica	14808-60-7	8-hour daily exposure limit (VLA_ED): 0.05 mg/m ³
Sweden	Heptane	142-82-5	Level Limit Value (NGV): 200 ppm (800 mg/m ³)
	Heptane	142-82-5	Short Term Limit (KTV): 300 ppm (1200 mg/m ³)
	Heptane	142-82-5	Short Term Limit (KTV): 300 ppm (1200 mg/m ³) - Work Environment Authority (AV), Occupational Exposure Limit Values (AFS 2018:1)
	Heptane	142-82-5	Level Limit Value (NGV): 200 ppm (800 mg/m ³) - Work Environment Authority (AV), Occupational Exposure Limit Values (AFS 2018:1)
	Zinc oxide	1314-13-2	Level Limit Value (NGV): 5 mg/m ³ (Total dust)
	Stearic acid	57-11-4	Level Limit Value (NGV): 5 mg/m ³ (as stearates, total dust)
	Titanium Dioxide	13463-67-7	OEL: (NGV) 5.0 (Total dust) mg/m ³
	Clay	1332-58-7	Level Limit Value (NGV): 5 mg/m ³ (respirable dust)
	Clay	1332-58-7	Level Limit Value (NGV): 10 mg/m ³ (inhalable dust)
	White Mineral Oil	8042-47-5	Level Limit Value (NGV): 1 mg/m ³ (Oil mist including oil fume)
	White Mineral Oil	8042-47-5	Short Term Limit (KTV): 3 mg/m ³ (Oil mist including oil fume)
	Crystalline Silica	14808-60-7	Level Limit Value (NGV): 0.1 mg/m ³ (quartz, respirable)
Luxembourg	Heptane	142-82-5	TWA: 500 ppm (2085 mg/m ³)
Austria	Heptane	142-82-5	TWA: 2000 mg/m ³ (500 ppm)
	Heptane	142-82-5	STEL: 8000 mg/m ³ (2000 ppm)
	Titanium Dioxide	13463-67-7	OEL: TWA 5 mg/m ³
	Titanium Dioxide	13463-67-7	OEL: STEL 10 mg/m ³
	Crystalline Silica	14808-60-7	MAK yearly average: 0.15 mg/m ³
Cyprus	Zinc oxide	1314-13-2	8-hour TWA: 5.0 mg/m ³ (Fumes)
	Titanium Dioxide	13463-67-7	OEL: TWA 10.0 mg/m ³ 8-hr

Biological limit values:

No biological exposure limits noted for the ingredient(s).

Derived No Effect Level (DNEL):

Not determined or not applicable.

Predicted No Effect Concentration (PNEC):

Not determined or not applicable.

Safety Data Sheet

According to Regulation (EC) No. 1272/2008 (CLP), as amended by Commission Regulation (EU) 2019/521 and Commission Delegated Regulation (EU) 2020/217, and (EC) No. 1907/2006 (REACH)

Initial preparation date: 06.04.2021

Page 14 of 22

Maxibond Blue Cement

Information on monitoring procedures:

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls
Biological monitoring may also be appropriate for some substances

8.2 Exposure controls

Appropriate engineering controls:

Emergency eye wash fountains and safety showers should be available in the immediate vicinity of use or handling.

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapor and mists below the applicable workplace exposure limits (Occupational Exposure Limits-OELs) indicated above.

Use explosion-proof ventilation equipment.

Personal protection equipment

Eye and face protection:

Safety goggles or glasses, or appropriate eye protection.

Skin and body protection:

Select glove material impermeable and resistant to the substance in compliance with European Standard EN 374 and/or EN 420. For continuous contact, we recommend nitrile gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. Glove thickness should be typically greater than 0.35 mm depending on the glove make and model. Always seek advice from glove suppliers.

Respiratory protection:

If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn.

Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection.

Use a European Standard EN149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced. Comply with the European Standard EN149.

General hygienic measures:

When handling chemical products, do not eat, drink or smoke. Wash hands after handling, before breaks, and at the end of the workday. Avoid contact with skin, eyes and clothing. Wash contaminated clothing before reuse. Perform routine housekeeping.

Environmental exposure controls:

Select controls based on a risk assessment of local conditions.

See section 6 for information on accidental release measures.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	Blue Viscous Liquid
Odor	Strong Solvent
Odor threshold	Not determined or not available.
pH	Not determined or not available.
Melting point/freezing point	Not determined or not available.
Initial boiling point/range	190° F (88° C)
Flash point (closed cup)	15° F (-9° C)
Evaporation rate	> 1 (n-BuAC = 1)
Flammability (solid, gas)	Not determined or not available.

Safety Data Sheet

According to Regulation (EC) No. 1272/2008 (CLP), as amended by Commission Regulation (EU) 2019/521 and Commission Delegated Regulation (EU) 2020/217, and (EC) No. 1907/2006 (REACH)

Initial preparation date: 06.04.2021

Page 15 of 22

Maxibond Blue Cement

Upper flammability/explosive limit	6.7% (V)
Lower flammability/explosive limit	1.2% (V)
Vapor pressure	119 mmHg at 20°C (68°F)
Vapor density	Not determined or not available.
Density	Not determined or not available.
Relative density	Not determined or not available.
Solubilities	Not determined or not available.
Partition coefficient (n-octanol/water)	Not determined or not available.
Auto/Self-ignition temperature	Not determined or not available.
Decomposition temperature	Not determined or not available.
Dynamic viscosity	Not determined or not available.
Kinematic viscosity	3000 cps
Explosive properties	Not determined or not available.
Oxidizing properties	Not determined or not available.

9.2 Other information

SECTION 10: Stability and reactivity

10.1 Reactivity:

Does not react under normal conditions of use and storage.

10.2 Chemical stability:

Stable under normal conditions of use and storage.

10.3 Possibility of hazardous reactions:

None under normal conditions of use and storage.

10.4 Conditions to avoid:

Excess heat, ignition source or flames.

10.5 Incompatible materials:

None known.

10.6 Hazardous decomposition products:

None known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

Substance data:

Name	Route	Result
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	oral	LD50 Rat: > 5000 mg/kg
	dermal	LD50 Rabbit: > 2000 mg/kg
	inhalation	LC50 Rat: > 4.42 mg/L (4 hr, vapor)
Heptane	inhalation	LC50 Rat: > 29.29 mg/L (4 hr)
	oral	LD50 Rat: > 5000 mg/kg
	dermal	LD50 Rabbit: > 2000 mg/kg

Safety Data Sheet

According to Regulation (EC) No. 1272/2008 (CLP), as amended by Commission Regulation (EU) 2019/521 and Commission Delegated Regulation (EU) 2020/217, and (EC) No. 1907/2006 (REACH)

Initial preparation date: 06.04.2021

Page 16 of 22

Maxibond Blue Cement

Skin corrosion/irritation

Assessment:

Causes skin irritation

Product data:

No data available.

Substance data:

Name	Result
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	Causes skin irritation.
Heptane	Causes skin irritation.

Serious eye damage/irritation

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data: No data available.

Respiratory or skin sensitization

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data: No data available.

Carcinogenicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

Substance data:

Name	Species	Result
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	Not applicable	The carcinogenic classification applies to naphtha streams containing >0.1% Benzene.
Crystalline Silica	Not applicable	Airborne particles of respirable size of Crystalline silica are known to cause cancer.
Titanium Dioxide	Not applicable	Airborne, unbound particles of respirable size of Titanium Dioxide are known to cause cancer.

International Agency for Research on Cancer (IARC):

Name	Classification
Titanium Dioxide	Group 3 - Not classifiable as to its carcinogenicity to humans
Crystalline Silica	Group 1 - Carcinogenic to humans

National Toxicology Program (NTP):

Name	Classification
Crystalline Silica	Known to be human carcinogens

Germ cell mutagenicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

Safety Data Sheet

According to Regulation (EC) No. 1272/2008 (CLP), as amended by Commission Regulation (EU) 2019/521 and Commission Delegated Regulation (EU) 2020/217, and (EC) No. 1907/2006 (REACH)

Initial preparation date: 06.04.2021

Page 17 of 22

Maxibond Blue Cement

Substance data:

Name	Result
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	The mutagenic classification applies to naphtha streams containing >0.1% Benzene.

Reproductive Toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data:

Name	Result
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	The classification as a reproductive toxicant only applies when the naphtha stream contains >3% toluene and/or n-hexane.

Specific target organ toxicity (single exposure)

Assessment:

May cause drowsiness or dizziness

Product data:

No data available.

Substance data:

Name	Result
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	May cause drowsiness or dizziness.
Heptane	May cause drowsiness or dizziness.

Specific target organ toxicity (repeated exposure)

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data:

Name	Result
Crystalline Silica	Component affects the lungs through repeated exposure.

Aspiration toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data:

Name	Result
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	May be fatal if swallowed and enters airways.
Heptane	May be fatal if swallowed and enters airways.

Information on likely routes of exposure:

No data available.

Symptoms related to the physical, chemical and toxicological characteristics:

Refer to Section 4 of this SDS.

Safety Data Sheet

According to Regulation (EC) No. 1272/2008 (CLP), as amended by Commission Regulation (EU) 2019/521 and Commission Delegated Regulation (EU) 2020/217, and (EC) No. 1907/2006 (REACH)

Initial preparation date: 06.04.2021

Page 18 of 22

Maxibond Blue Cement

Other information:

No data available.

SECTION 12: Ecological information

12.1 Toxicity

Acute (short-term) toxicity

Assessment:

Toxic to aquatic life

Product data: No data available.

Substance data:

Name	Result
Zinc oxide	Oncorhynchus mykiss (rainbow trout) - 1.1 mg/l - 96.0 h
	Daphnia magna (Water flea) - 0.098 mg/l - 48 h
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	ErC50 Selenastrum capricornutum: 3.1 mg/L (72 hr)
	EC50 Daphnia magna: 4.5 mg/L (48 hr)
Heptane	EC50 Daphnia magna: 1.5 mg/L (48 hr)

Chronic (long-term) toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

Substance data:

Name	Result
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	EC50 Daphnia magna: 10 mg/L (10 days)
Heptane	NOEC Oncorhynchus mykiss: 1.28 mg/L (28 days)

12.2 Persistence and degradability

Product data: No data available.

Substance data:

Name	Result
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	Standard tests for this endpoint are intended for single substances and are not appropriate for this complex substance (UVCB).
Heptane	Readily biodegradable in water.

12.3 Bioaccumulative potential

Product data: No data available.

Substance data:

Name	Result
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	Standard tests for this endpoint are intended for single substances and are not appropriate for this complex substance (UVCB).
Heptane	Calculated BCF: 552 (Not expected to bioaccumulate).

12.4 Mobility in soil

Product data: No data available.

Substance data:

Name	Result
Heptane	Moderately Mobile (log Koc: 2.38)

Safety Data Sheet

According to Regulation (EC) No. 1272/2008 (CLP), as amended by Commission Regulation (EU) 2019/521 and Commission Delegated Regulation (EU) 2020/217, and (EC) No. 1907/2006 (REACH)

Initial preparation date: 06.04.2021

Page 19 of 22

Maxibond Blue Cement

12.5 Results of PBT and vPvB assessment

PBT assessment:

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	This substance is not PBT.
Heptane	This substance is not PBT.

vPvB assessment:

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	This substance is not vPvB.
Heptane	This substance is not vPvB.

12.6 Other adverse effects: No data available.

SECTION 13: Disposal considerations


13.1 Waste treatment methods

Relevant information:


Consult with EU Directive 2008/98/EC for the classifications of hazardous waste prior to disposal. Furthermore, consult with your regional, national or European waste requirements or guidelines, if applicable, to ensure compliance. Final decisions on the appropriate waste management method, in line with regional, national and European legislation, remains the responsibility of the waste treatment operator

SECTION 14: Transport information

International Carriage of Dangerous Goods by Road/Rail (ADR/RID)

UN number	UN1133
UN proper shipping name	Adhesives
UN transport hazard class(es)	3 
Packing group	II
Environmental hazards	Marine Pollutant (Heptane and Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics)
Special precautions for user	None

International Carriage of Dangerous Goods by Inland Waterways (ADN)

UN number	UN1133
UN proper shipping name	Adhesives
UN transport hazard class(es)	3 
Packing group	II
Environmental hazards	Marine Pollutant (Heptane and Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics)
Special precautions for user	None

Safety Data Sheet


According to Regulation (EC) No. 1272/2008 (CLP), as amended by Commission Regulation (EU) 2019/521 and Commission Delegated Regulation (EU) 2020/217, and (EC) No. 1907/2006 (REACH)

Initial preparation date: 06.04.2021


Page 20 of 22

Maxibond Blue Cement

International Maritime Dangerous Goods (IMDG)

UN number	UN1133
UN proper shipping name	Adhesives
UN transport hazard class(es)	3 
Packing group	II
Environmental hazards	Marine Pollutant (Heptane and Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics)
Special precautions for user	None

International Air Transport Association Dangerous Goods Regulations (IATA-DGR)

UN number	UN1133
UN proper shipping name	Adhesives
UN transport hazard class(es)	3 
Packing group	II
Environmental hazards	Marine Pollutant (Heptane and Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics)
Special precautions for user	None

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code

Bulk Name	None
Ship type	None
Pollution category	None

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture.

European regulations

Inventory listing (EINECS):

35884-05-0	Zinc Dibutyldithiocarbamate/Butylamine Complex	Listed
1314-13-2	Zinc oxide	Listed
57-11-4	Stearic acid	Listed
13463-67-7	Titanium Dioxide	Listed
65997-13-9	Glycerol Ester of Partially Hydrogenated Wood Rosin	Listed
1332-58-7	Clay	Listed
8042-47-5	White Mineral Oil	Listed
64742-49-0	Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	Listed
14808-60-7	Crystalline Silica	Listed
142-82-5	Heptane	Listed

REACH SVHC candidate list: None of the ingredients are listed.

REACH SVHC Authorizations: None of the ingredients are listed.

REACH Restriction: None of the ingredients are listed.

Safety Data Sheet

According to Regulation (EC) No. 1272/2008 (CLP), as amended by Commission Regulation (EU) 2019/521 and Commission Delegated Regulation (EU) 2020/217, and (EC) No. 1907/2006 (REACH)

Initial preparation date: 06.04.2021

Page 21 of 22

Maxibond Blue Cement

Water hazard class (WGK) (Product): Not determined.

Water hazard class (WGK) (Substance):

Ingredient Name	CAS	Class
Zinc oxide	1314-13-2	2
Stearic acid	57-11-4	Non-hazardous to water.
Titanium Dioxide	13463-67-7	Non-hazardous to water.
Glycerol Ester of Partially Hydrogenated Wood Rosin	65997-13-9	1
Clay	1332-58-7	Non-hazardous to water.
White Mineral Oil	8042-47-5	1
Crystalline Silica	14808-60-7	Non-hazardous to water.
Zinc Dibutyldithiocarbamate/Butyl amine Complex	35884-05-0	Not applicable.
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	64742-49-0	2
Heptane	142-82-5	2

Other regulations

Germany TA Luft: Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics: Class I; Mass flow: 0.1 kg/hr; Maximum Concentration Allowed if Emissions Exceed Base Rate: 20 mg/m³

Germany MAK: Zinc oxide: 8-hour TWA: 0.1 mg/m³ [Zinc and its inorganic compounds (respirable fraction)], Heptane: 8-hour TWA: 500 ppm (2100 mg/m³), Zinc oxide: 8-hour TWA: 2 mg/m³ [Zinc and its inorganic compounds (inhalable fraction)], Kaolin: 8-hour TWA: 0.3 mg/m³

15.2 Chemical Safety Assessment

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

SECTION 16: Other information

Indication of changes:

Not applicable.

Abbreviations and Acronyms: None

Classification procedure:

Classification according to Regulation (EC) No. 1272/2008 (CLP)	Method Used
Flammable liquids, category 2	Calculation method
Skin irritation, category 2	Calculation method
Specific target organ toxicity - single exposure, category 3, central nervous system	Calculation method
Chronic aquatic hazard, category 2	Calculation method

Safety Data Sheet

According to Regulation (EC) No. 1272/2008 (CLP), as amended by Commission Regulation (EU) 2019/521 and Commission Delegated Regulation (EU) 2020/217, and (EC) No. 1907/2006 (REACH)

Initial preparation date: 06.04.2021

Page 22 of 22

Maxibond Blue Cement

Summary of classification(s) in section 3:

Stot SE 3; H336	Specific target organ toxicity - single exposure, category 3, central nervous system
Asp. Tox. 1; H304	Aspiration hazard, category 1
Aquatic Chronic 2; H411	Chronic aquatic hazard, category 2
Skin Irrit. 2 ; H315	Skin irritation, category 2
Flam. Liq. 2; H225	Flammable liquids, category 2
Aquatic Acute 1; H400	Acute aquatic hazard, category 1
Aquatic Chronic 1; H410	Chronic aquatic hazard, category 1
Stot RE 1; H372	Specific target organ toxicity - repeated exposure, category 1
Carc. 1A; H350	Carcinogenicity, category 1A

Summary of hazard statements in section 3:

H336	May cause drowsiness or dizziness
H304	May be fatal if swallowed and enters airways
H411	Toxic to aquatic life with long lasting effects
H315	Causes skin irritation
H225	Highly flammable liquid and vapour
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H372	Causes damage to organs through prolonged or repeated exposure
H350	May cause cancer

Disclaimer:

This product has been classified in accordance with EC No. 1272/2008 (CLP), as amended by Commission Regulation (EU) 2019/521 and Commission Delegated Regulation (EU) 2020/217, and EC No. 1907/2006 (REACH). The information provided in this SDS is correct, to the best of our knowledge, based on information available. The information given is designed only as a guidance for safe handling, use, storage, transportation, and disposal and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials, unless specified in the text. The responsibility to provide a safe workplace remains with the user.

Initial preparation date: 06.04.2021

End of Safety Data Sheet