Color	black / white			transparent	Runflat
	soft	universal	hard	soft, universal, hard	universal
Consistency	creamy, soft	creamy, medium	firm	See left	creamy, medium
Content	5 kg	5 kg	5 kg	5 kg	5 kg
Application	Best pick-up with brush easy installation due to high gliding properties For cold temperatures	Good absorption through brushes For cold to moderately warm temperatures	Economical pick- up by brush with high tire throughput Due to the high viscosity, the paste does not flow away during application and is therefore more economical In general: the larger the tire, the harder the paste should be for warm temperatures	Advantages soft, univer-sal and hard see left Can be used very spa-ringly as a film former due to its high glycerine content and therefore high yield	For runflat tires and sporty vehicles Extra high gliding properties
Consumption (for how many tires?)	High	Medium	Economical/ low	See left (We recommend sparing application due to the high glycerine content)	Economical/ low
Lubricity	High	High	High	Very high	Very high
Drying behavior	Quick drying	Quick drying	Quick drying	Slow drying, transparent little residue	Slow drying (idea for parallel processing of tire
Biodegradeble	Yes	Yes	Yes	Yes	Yes
	Chemically neutral towards rubber, steel & aluminum				
Processing temperature	-10 to +50°C	-10 to +50°C	-10 to +50°C	-10 to +50°C	-15 to +50°C
Vehicle types					



MOUNTING PASTES

THREE VISCOSITIES: SOFT, UNIVERSAL, HARD

The right consistency for every application.

IDEAL FOR DISASSEMBLY

Simply coat narrow areas.

TRANSPARENT

No cleaning necessary after installation.

HIGH LUBRICITY

For easy mounting & tight fit of the tire.

VEGAN

HARD

All mounting pastes are environmentally friendly and biodegradable.

Transparent Universal Art.-Nr.: 3401-0505-003



Black Universal Art.-Nr.: 3401-0505-101 White Universal Art.-Nr.: 3401-0505-001 Runflat

Art.-Nr.: 3404-0023-093



Black Hard Art - Nr: 3401-0507-101

White Hard Art.-Nr.: 3401-0507-001



Black Soft Art.-Nr.: 3401-0503-101

White Soft Art.-Nr.: 3401-0503-001