



With precise calibration to the perfect air pressure








With precise calibration to the perfect air pressure. Our tyre inflation device **GATOR INFLATOR MID** is already calibrated. What does this imply? Immediate operational availability and highest quality! No additional effort, no additional fees. Just pick it up and get started!

The tyre inflator complies with the harmonised European standard for tyre pressure gauges.


✔ Type tested

✔ Conformity tested

TECHNICAL DATA:

 Weight	730 g
 Filling medium	air / nitrogen
 Max. permissible operating pressure	16 bar / 230 psi
 Pressure gauge measurement range	0 - 12 bar / 170 psi analogue pressure gauge
 Temperature range	-20°C to +55°C
 Pressure gauge display accuracy	pm ≤ 4 bar: ±0,08 bar 4 bar < pm ≤ 10 bar: ±0,16 bar pm > 10 bar: ±0,25 bar
 Pressure gauge graduation	0,1 bar / 2 psi

EVOLUTION OF AIR CONTROL



WEGMANN automotive GmbH
Rudolf-Diesel-Straße 6
97209 Veitshöchheim
Germany

Phone: +49 (0) 931-32104-0
E-Mail: info@wegmann-automotive.com
Internet: www.wegmann-automotive.com

GATOR INFLATOR MID

The tyre filler for professionals

FOR ALL PROFESSIONALS

Simple. Reliable. Multifunctional.

SIMPLE

Due to the suspension eye, the device is always well placed and close at hand. With its flexible tube and the easy handling of the operating lever, tyre inflation is easier than ever before - even with one hand.

RELIABLE

Due to the calibration of the pressure gauge and the precise processing the **GATOR INFLATOR MID** always delivers reliable measurement results. German Engineering.

MULTIFUNCTIONAL

The valve adapter for all common plug variants and a measuring range of up to 16 bar make the **GATOR INFLATOR MID** a multifunctional device. The exchangeable hose lengths also enable the access of difficult placed valves.

Operation lever

made of metal for a easy handling even with one hand!

Suspension eye

for simple and fast storage

Calibrated pressure gauge

for a precise measurement of the air pressure. Made in Germany

Ruber handle

non-slip rubber handle sheathed aluminium

Valve adapter

multifunctional for all common connector versions

Quick coupling

(thread G3/8)

flexible use through variable plug nipples

Compressed air hose

flexible rubber hose for an ergonomic working position
Length: 0,5 m or 1 m

